

# Serenade™

ROMAN SHADES



www.vasawindowcoverings.com  
 2205 W Braker Ln Austin TX 78758  
 tel: 512.835.0100 800.708.0243  
 fax: 512.835.0108

BILL TO:

Company Name: \_\_\_\_\_ Acct #: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 City / State / Zip: \_\_\_\_\_  
 Phone: \_\_\_\_\_  
 Fax Number: \_\_\_\_\_

SHIP TO:

Company Name: \_\_\_\_\_ Acct #: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 City / State / Zip: \_\_\_\_\_  
 Phone: \_\_\_\_\_  
 Fax Number: \_\_\_\_\_

P.O. #: \_\_\_\_\_  
 Side Mark: \_\_\_\_\_  
 Contact: \_\_\_\_\_  
 Date: \_\_\_\_\_

Style (circle one)	Model* (circle one)				Qty	Color #	Color Name	Width	Length	Mount	Cord		2 on 1** Headrail Yes/No	Omni-Rise Only Cord Loop 2' - 15'	Designer Valance		Designer Valance Only Custom Return Size	Special Instructions
											Right	Left			Y	N		
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	
Clas	Flat	Std	Duofold	OmniRise						IB	OB	R	L	Y	N	Y	N	

\* Some sizes and fabrics must be built with the Omni-Rise System, see price list for details. \*\* Two On One Shades are available in Classic Roman Style only.  
 Note in Special Instructions for items like Hold Downs, Extension Brackets, Motors and Remotes etc.

**Measuring Instructions**

**Inside Mount**

1. Measure across the width of your window opening at three places - top, middle, and bottom. Measurements should be taken within the window jamb. Provide the smallest of the three measurements to Comfortex. Comfortex will make the necessary deductions to fit in your window opening. Comfortex will deduct approximately 3/8" for clearance.

2. Measure the length of the window opening from the soffit to the surface of the window sill in two places - use the smallest of these two measurements.

**Outside or Projection Mount**

1. Measuring the exact width and length of the area to be covered. On the width, many prefer to measure the exact width of the opening and add four inches (2" to each side) to ensure privacy.

2. Projection brackets allow shades to be mounted up to four inches away from the mounting surface. Please specify projection mount when ordering. Projection mounts are recommended for outside mounts only.

3. Be sure to take into consideration, any obstructions such as window trim, molding, locks and window cranks.

**Shipping Charges** - The freight on all blind orders within size and weight limitations of UPS will be prepaid. Boxed blinds, valances that do not meet the UPS size and weight requirement will ship common carrier. There will be a direct common carrier fee of \$40.00 for each order that requires this mode of transportation. A per unit transportation charge will be added to all orders.

Customer Signature \_\_\_\_\_ Date \_\_\_\_/\_\_\_\_/\_\_\_\_ Measured By \_\_\_\_\_ Date \_\_\_\_/\_\_\_\_/\_\_\_\_